


口 径	φ75~φ700		
沈下(偏心)量	100mm~500mm		
内 圧	中圧用	常用圧力 (W.P) =0.50MPa	試験圧力 (T.P) =0.75MPa
口金形状	両フランジ		



呼 径	偏心量 100mm(F・F) 中圧用 SJ-K100S				価 格
	面 長	山 数	伸 び	縮 み	
75(80)	500	3	40	30	154,000
100	500	3	50	30	189,000
125	500	3	50	30	204,000
150	500	3	50	40	277,000
200	500	3	50	40	333,000
250	550	3	50	40	370,000
300	550	3	50	40	434,000
350	600	3	60	40	541,000
400	600	3	60	40	602,000
450	600	3	60	40	675,000
500	600	3	60	40	776,000
600	650	3	90	70	1,091,000
700	650	3	90	70	1,301,000

呼 径	偏心量 200mm(F・F) 中圧用 SJ-K200S				価 格
	面 長	山 数	伸 び	縮 み	
75(80)	700	4	60	40	187,000
100	700	4	70	40	217,000
125	700	4	70	40	233,000
150	700	4	70	50	316,000
200	700	4	70	50	382,000
250	700	4	70	50	437,000
300	700	4	70	50	505,000
350	750	4	80	50	627,000
400	750	4	80	50	692,000
450	750	4	80	50	750,000
500	750	4	80	50	898,000
600	800	4	120	90	1,269,000
700	800	4	120	90	1,480,000